

TECHNICAL SPECIFICATIONS

	H50-500	H150-1000N	H150-1500NS	H150-2100NS	H150-3000NS
Temperature range (°C)	-5 ~ +35	+8 ~ +35	+8 ~ +35	+8 ~ +35	+8 ~ +35
Temperature stability (°C)	±0,3	±0,1	±0,1	±0,1	±0,1
Temperature control mode	PID	PID	PID	PID	PID
Cooling capacity (W)	500	1000	1500	2100	3000
Pump flux (L/min)	3 @10psi	5 @60psi	5 @60psi	13 @60psi	13 @60psi
Pump power (W)	25	120	120	250	250
Pump type	Magnetic	Magnetic	Magnetic	Magnetic	Magnetic
Heat exchanger model	Board	Board	Board	Board	Board
Dimension mm (LxWxH cm)	480x250x500	560x360x590	650x385x625	735x460x703	735x460x703
Weight (Kg)	28	55	78	92	92
Power supply voltage	230V, 50/60Hz	230V, 50/60Hz	230V, 50/60Hz	230V, 50/60Hz	230V, 50/60Hz
Ordering information	LW500	LW1000N	LW1500NS	LW2100NS	LW3000NS

	H150-5000N	H150-7000N	H150-9000N	H150-1000NLT	H150-2100NSLT
Temperature range (°C)	+8 ~ +35	+8 ~ +35	+8 ~ +35	-20 ~ +35	-20 ~ +35
Temperature stability (°C)	±0,2	±0,2	±0,2	±0,1	±0,1
Temperature control mode	PID	PID	PID	PID	PID
Cooling capacity (W)	5000	7000	9000	1000	2100
Pump flux (L/min)	13 @60psi	13 @60psi	13 @60psi	5 @60psi	13 @60psi
Pump power (W)	250	250	250	120	250
Pump type	Magnetic	Magnetic	Magnetic	Magnetic	Magnetic
Heat exchanger model	Board	Board	Board	Board	Board
Dimension mm (LxWxH cm)	690x640x1100	690x640x1100	690x640x1100	560x360x590	735x460x703
Weight (Kg)	170	170	170	55	92
Power supply voltage	230V, 50/60Hz	230V, 50/60Hz	230V, 50/60Hz	230V, 50/60Hz	230V, 50/60Hz
Ordering information	LW5000N	LW7000N	LW9000N	LW1000NLT	LW2100NSLT

Customized versions available